



ST 8000 Series All-in-One Touch POS System



General Features	<ul style="list-style-type: none"> * Good Flexibility Design suitable for various applications * Flexible expansion provides PCI bus slot x 3 and AGP 3.0 (AGP 8X) slot * 3 Extra Drive bays, including two 3.5" and one 5.25" drivers(2 x 3.5" for Hybrid Card Reader / Floppy 1 x 5.25" for DVD-R(W) /CD-R(W)) * Extremely Solid and Reliable structure * Water spill proof * Tilt Angle 0° ~ 45°: Adapt to operation in any environment. * OSD and Power Switch Control Panel on the rear * Removable Base and Wall Mounting capability with 75mm VSEA holes 	
Specification	MODEL	ST-8000
Motherboard	Form Factor	Micro ATX (244 x 205mm)
	CPU Type	Pentium D/ Pentium IV /Celeron D LGA Performance Platform or AMD Athlon 64 at 1000MHz
	System Freq	533/800/1066 MHz
	Chipset	VIA P4M800+ 8237R plus
	Memory	Two 240-PIN DDR 400/533 MHz (Non-ECC up to 2GB)
	Video	Int. VIA UniChrome Pro Graphic
	Ethernet	VIA VT6103 10/100 PHY
	Audio	VIA VT1616-CH audio codec S/PDIF (header)
	Storage Device	3.5" IDE HDD x 1 (Support Ultra ATA 66/100/133, DMA and PIO)
I/O Connector		Serial Port x2+ 6 Optional
		Parallel Port x 1
		USB 2.0 Port x 4+ 4 Optional
		PS/2 Mouse Port x 1 PS/2 Keyboard port x 1
		VGA Port x1
		RJ-45 Ethernet Port x1
		Audio Line in/Speaker-out/Mic-in Jackx1
	Monitor	17" SXGA TFT LCD
	Touch Screen	TW 5-wire or ELO Resistive Touch Screen(RS-232or USB interface)
	Power Supply	Internal 250W Power Supply
	Dimension(mm)	426(W) x 219(D) x 405(H) mm
	Optional Integrated Device	MSR, VFD Customer Display, Second 12",14",15",17" monitor